

● Standard type model number list (full-cone pattern type)

| Model | Model number | Min. orifice diameter [mm] | Flow rate [L/min] at following pressure [MPa] | | | | | | Spray angle at following pressure [MPa] | | | |
|-------|--------------|----------------------------|---|------|------|------|------|-----|---|-----|-----|-----|
| | | | 0.1 | 0.2 | 0.3 | 0.5 | 0.7 | 0.7 | 0.3 | 0.5 | 0.7 | |
| KSF | 00860 | 0.5 | 0.50 | 0.67 | 0.80 | 1.00 | 1.15 | 0.1 | 51° | 60° | 53° | 40° |
| | 00890 | 0.5 | 0.50 | 0.67 | 0.80 | 1.00 | 1.15 | 80° | 90° | 74° | 56° | |
| | 0160 | 0.5 | 0.62 | 0.84 | 1.00 | 1.25 | 1.44 | 51° | 60° | 53° | 40° | |
| | 0190 | 0.5 | 0.62 | 0.84 | 1.00 | 1.25 | 1.44 | 80° | 90° | 74° | 56° | |
| | 01560 | 0.5 | 0.94 | 1.26 | 1.50 | 1.87 | 2.2 | 51° | 60° | 53° | 40° | |
| | 01590 | 0.5 | 0.94 | 1.26 | 1.50 | 1.87 | 2.2 | 80° | 90° | 74° | 56° | |
| | 0260 | 0.5 | 1.25 | 1.68 | 2.0 | 2.5 | 2.9 | 51° | 60° | 53° | 40° | |
| | 0290 | 0.5 | 1.25 | 1.68 | 2.0 | 2.5 | 2.9 | 80° | 90° | 74° | 56° | |