

● Standard type model number list (flat pattern type)

Model	Model number	Min. orifice diameter [mm]	Flow rate [L/min] at following pressure [MPa]					Spray angle at following pressure [MPa]				
			0.1	0.2	0.3	0.5	0.7	0.1	0.2	0.3	0.5	0.7
KSS	00740	0.6	0.40	0.57	0.70	0.90	1.07	30°	36°	40°	44°	46°
	00760	0.5	0.40	0.57	0.70	0.90	1.07	46°	55°	60°	64°	66°
	00780	0.4	0.40	0.57	0.70	0.90	1.07	65°	75°	80°	85°	87°
	0140	0.8	0.58	0.82	1.00	1.29	1.53	30°	36°	40°	44°	46°
	0160	0.7	0.58	0.82	1.00	1.29	1.53	47°	55°	60°	64°	66°
	0180	0.6	0.58	0.82	1.00	1.29	1.53	66°	75°	80°	85°	87°
	01540	0.9	0.87	1.22	1.00	1.94	2.3	31°	36°	40°	44°	46°
	01560	0.7	0.87	1.22	1.50	1.94	2.3	49°	55°	60°	65°	66°
	01580	0.6	0.87	1.22	1.50	1.94	2.3	67°	75°	80°	85°	87°
	0240	1.0	1.15	1.63	1.50	2.6	3.1	31°	36°	40°	44°	46°
	0260	0.8	1.15	1.63	2.0	2.6	3.1	49°	55°	60°	65°	66°
	0280	0.7	1.15	1.63	2.0	2.6	3.1	67°	75°	80°	85°	87°