

● Standard type model number list

Criterion water flow rate [L/h]	Air flow rate [m ³ /h(nor)]	Spray angle	Model number of nozzle tip	Model number of mixing body	Min. orifice diameter for liquid [mm]
50	7.5	30°	1/4 KSAMD 105 × 8-30	1/4 A25 1/4 W14	1.05
		60°	1/4 KSAMD 105 × 8-60		
		90°	1/4 KSAMD 105 × 8-90		
70	10.5	30°	1/4 KSAMD 13 × 8-30	1/4 A29 1/4 W16	1.3
		60°	1/4 KSAMD 13 × 8-60		
		90°	1/4 KSAMD 13 × 8-90		
100	15.0	30°	1/4 KSAMD 16 × 8-30	1/4 A35 1/4 W19	1.6
		60°	1/4 KSAMD 16 × 8-60		
		90°	1/4 KSAMD 16 × 8-90		
150	22.5	30°	1/4 KSAMD 21 × 8-30	1/4 A42 1/4 W23	2.1
		60°	1/4 KSAMD 21 × 8-60		
		90°	1/4 KSAMD 21 × 8-90		
200	30	30°	3/8 KSAMD 22 × 8-30	3/8 A48 3/8 W27	2.2
		60°	3/8 KSAMD 22 × 8-60		
		90°	3/8 KSAMD 22 × 8-90		
300	45	30°	3/8 KSAMD 27 × 8-30	3/8 A62 3/8 W35	2.7
		60°	3/8 KSAMD 27 × 8-60		
		90°	3/8 KSAMD 27 × 8-90		

* The criterion water flow rate is a value of air pressure 0.3 MPa or less, water pressure 0.3 MPa or less, and air-water volume ratio 150.